

The economy dispensers for routine dispensing.
Precise, rugged, low-cost.



seripettor® seripettor® *pro*

F I R S T C L A S S · B R A N D


- Low-cost replaceable dispensing cartridge and valves!
- Easy cleaning and maintenance!
- Easy to operate!
- Refills automatically!
- Volume range from 0.2 to 25 ml

seripettor®:

for dispensing alkaline, buffer and vitamin solutions, as well as culture media, e.g., agar nutrient medium, up to 60 °C

seripettor® *pro*:

broader scope of application compared to the seripettor®; for dispensing many acidic, alkaline and saline solutions, and solvents



The low-cost alternative...




seripettor® and **seripettor® pro** are innovative bottle-top dispensers from BRAND with a special design. A lifting spring provides automatic filling. When the piston seal is worn out, the entire dispensing unit can be exchanged by the user rapidly and problem-free.

seripettor® and **seripettor® pro** open up an enormous range of applications in routine lab work, with dispensing of buffer solutions, culture media, vitamin solutions; acid, alkaline or salt solutions, and many polar solvents. Even special cases can be managed; for example, the **seripettor®** can handle agar culture media up to a max. of 60 °C. A guide for selecting the right equipment can be found on the last page.

Eliminate expensive repairs! Dissassembles without tools.

The innovative design of **seripettor®** / **seripettor® pro** makes cleaning and maintenance easy. All parts can be replaced quickly without tools.

A closer look...



Volume settings

Scalloped track allow for quick and exact setting of desired volume. The selected volume can be easily read.



Semi-automatic dispensing

The spring-loaded piston refills the cylinder after dispensing.



Replaceable dispensing cartridge

In the event of contamination with crystallizing or sticky deposits, the dispensing cartridge is easy and inexpensive to replace. One spare cartridge included free!



Fits most bottles

Valve block (45 mm) and included adapters (32 and 40 mm) match the threads of the most common reagent bottles.

Handling



Dispensing

For dispensing, press down gently on the piston. Filling takes place automatically, thanks to the spring.



Serial dispensing

The optional flexible discharge tube with the safety grip makes it easier to dispense in long series (it connects to the valve block with an adapter).



Accessories for dispensing sterile liquids

1. Mount the valve block with filling tube onto the bottle and cover the valve block with cap. Fix the autoclavable sterile membrane filter (0.2 µm) laterally and autoclave at 121 °C.
2. On a Clean-bench (sterile hood), remove the cap from the valve block, screw in a new sterile dispensing cartridge and mount the pump assembly. You're ready to dispense!



Materials of Construction

	seripettor®	seripettor® pro
Pump assembly	PC	PPO/PEI (for UV protection)
Lifting spring	spring steel	Hastalloy (stainless)
Dispensing cartridge*	PE/PP	PE/PP
Valve block*	PP	PP
Valve*	PP/EPDM	ETFE/borosilicate glass/Al ₂ O ₃ /Pt-Ir
Discharge tube*	FEP	PTFE/ETFE/FEP/PFA/borosilicate glass/Al ₂ O ₃ /Pt-Ir
Filling tube*	PP	Telescoping filling tube, FEP/PTFE
Cap for discharge tube*	Stopper cap, PP	Screw cap, PP

* parts in contact with the media

Operating Limits

	seripettor®	seripettor® pro
Vapor pressure	up to 500 mbar	up to 500 mbar
Density	up to 2.2 g/cm ³	up to 2.2 g/cm ³
Temperature	15 to 40 °C, agar cultures up to 60 °C	15 to 40 °C
Viscosity	2 ml instrument: 300 mm ² /s 10 ml instrument: 150 mm ² /s 25 ml instrument: 75 mm ² /s	2 ml instrument: 300 mm ² /s 10 ml instrument: 150 mm ² /s 25 ml instrument: 75 mm ² /s

Ordering Data

Items supplied:

seripettor®/seripettor® pro, discharge tube, filling tube, spare dispensing cartridge and adapter, PP (GL 45/32 and GL 45/S40).

	seripettor®			seripettor® pro		
	0.2 - 2	1 - 10	2.5 - 25	0.2 - 2	1 - 10	2.5 - 25
Volume (ml)	0.2 - 2	1 - 10	2.5 - 25	0.2 - 2	1 - 10	2.5 - 25
Subdivision (ml)	0.04	0.2	0.5	0.04	0.2	0.5
A* (±) %	1.2	1.2	1.2	1.2	1.2	1.2
µl	24	120	300	24	120	300
CV* (≤) %	0.2	0.2	0.2	0.2	0.2	0.2
µl	4	20	50	4	20	50
Cat. No.	4720 120	4720 140	4720 150	4720 420	4720 440	4720 450

* All dispensers calibrated to deliver (TD, Ex). Error limits according to the nominal capacity (= maximum volume) indicated on the instrument, obtained with instrument and distilled water at equilibrium with ambient temperature at 20 °C, and with smooth, steady operation. A = Accuracy, CV = Coefficient of variation

Accessories

Dispensing cartridges

Non-sterile and sterile piston (PE), cylinder (PP).



Flexible discharge tube

PTFE, coiled, length 800 mm, with handle. Not suitable for HF and peroxides. Pack of 1.



Description	Pack of	Cat. No.	Nominal volume	Cat. No.
2 ml, non-sterile	3	7045 00	2 + 10 ml	7045 22
10 ml, non-sterile	3	7045 02	25 ml	7045 23
25 ml, non-sterile	3	7045 04		
2 ml, sterile (individually wrapped)	7	7045 07		
10 ml, sterile (individually wrapped)	7	7045 06		
25 ml, sterile (individually wrapped)	5	7045 08		



Dispenser selection chart

Reagent	seripettor®	seripettor® pro	Reagent	seripettor®	seripettor® pro	Reagent	seripettor®	seripettor® pro
Acetaldehyde		+	Calcium hydroxide	+	+	Nitric acid, 10%		+
Acetic acid, 5%	+	+	Calcium hypochlorite		+	Oxalic acid	+	+
Acetic acid, 96%		+	Chloroacetaldehyde, 45%		+	Perchloric acid		+
Acetic acid (glacial), 100%		+	Chloroacetic acid		+	Phenol		+
Acetone		+	Chromic acid, 50%		+	Phosphoric acid, 85%		+
Acetonitrile		+	Copper sulfate	+	+	Piperidine		+
Acetophenone	+		Cumene (Isopropyl benzene)		+	Potassium chloride	+	+
Acetylacetone	+	+	Diethylene glycol	+	+	Potassium dichromate	+	+
Acrylic acid		+	Dimethyl sulfoxide (DMSO)		+	Potassium hydroxide	+	+
Acrylonitrile		+	Dimethylaniline		+	Potassium hydroxide in ethanol	+	+
Adipic acid	+	+	Ethanol	+	+	Potassium permanganate	+	+
Agar (60 °C)	+		Formaldehyde, 40%	+	+	Propionic acid	+	+
Allyl alcohol	+	+	Formamide	+	+	Propylene glycol (Propanediol)	+	+
Aluminium chloride	+	+	Formic acid, 100%		+	Pyridine		+
Amino acids	+	+	Glycerol	+	+	Pyruvic acid	+	+
Ammonia, 30%	+	+	Glycol (Ethylene glycol)	+	+	Salicylaldehyde		+
Ammonium chloride	+	+	Glycolic acid, 50%	+	+	Salicylic acid	+	+
Ammonium fluoride	+	+	Hexanoic acid	+	+	Silver acetate	+	+
Ammonium sulfate	+	+	Hexanol		+	Silver nitrate	+	+
Amyl alcohol (Pentanol)	+	+	Hydriodic acid	+	+	Sodium acetate	+	+
n-Amyl acetate		+	Hydrobromic acid		+	Sodium chloride	+	+
Aniline		+	Hydrochloric acid, 37%		+	Sodium dichromate	+	+
Barium chloride	+	+	Hydrogen peroxide, 35%	+		Sodium fluoride	+	+
Benzaldehyde		+	Isoamyl alcohol		+	Sodium hydroxide, 30%	+	+
Benzyl alcohol		+	Isobutanol	+	+	Sodium hypochlorite 20% (active chlorine approx. 10%)		+
Benzylamine		+	Isopropanol (2-Propanol)	+	+	Sulfuric acid, 10%	+	+
Benzylchloride		+	Lactic acid	+	+	Tartaric acid		+
Boric acid, 10%	+	+	Methanol	+	+	Urea	+	+
Butanediol	+	+	Methyl benzoate		+	Zinc chloride, 10%	+	+
1-Butanol		+	Methyl ethyl ketone		+	Zinc sulfate, 10%	+	+
Butylamine		+	Methyl propyl ketone		+			
n-Butyl acetate		+	Mineral oil (Engine oil)		+			
Calcium carbonate	+	+	Monochloroacetic acid		+			
Calcium chloride	+	+						

Note: seripettor® and seripettor® pro are not suitable for HF.

The above recommendations reflect testing completed prior to publication. Always follow instructions in the operating manual of the instrument as well as the reagent manufacturer's specifications. In addition to these chemicals, a variety of organic and inorganic saline solutions (e.g., biological buffers), biological detergents and media for cell culture can be dispensed. Should you require information on chemicals not listed, please feel free to contact BRAND. Status as of: 0614/8

Additional information on the seripettor® and seripetto® pro (operating manual, etc.) can be found at www.brand.de

BRAND®, seripettor® and seripetto® pro are trademarks of BRAND GMBH + CO KG, Germany.

Our technical literature is intended to inform and advise our customers. However, the validity of general empirical values, and of results obtained under test conditions, for specific applications depends on many factors beyond our control. Please appreciate, therefore, that no claims can be derived from our advice. The user is responsible for checking the appropriateness of the product for any particular application.

Subject to technical modification without notice. Errors excepted.

BRAND GMBH + CO KG · P.O. Box 11 55 · 97861 Wertheim · Germany
Phone: +49 9342 808-0 · Fax: +49 9342 808-98000 · E-Mail: info@brand.de · Internet: www.brand.de

